



Directive 2002/95/EC
"RoHS"
Compliant

Notes:

1. Electrical:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Operating Temperature: -40° C to +85° C
2. Materials and Finish:
 - Coupling Ring: Polyester (Black), Metallized ABS or Die-cast (Nickel Plated); UL94 V-0
 - Plug Housing: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
 - Interfacial Seal: Silicone, Color: White
 - Cable Gland: PA (Black) or Brass, Nickel Plated
 - Cable Gland Seal: NBR, Color: Black
 - Cable Gland Insert (Metal Version): Nylon, Color: White
 - RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
 - RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-0
 - RJ45 Plug Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
 - Cable: UTP or STP Cat. 5e AWG24 Solid, Color: Black
3. RoHS compliant

L	Part Number		
	Plastic Version with Unshielded Cable	Metallized Plastic Version with Shielded Cable	Die-Cast Version with Shielded Cable
2 M	17-10003	17-10025	17-100514
4 M	17-10004	17-10026	17-100524
5 M	17-10005	17-10027	17-100534

THIS DRAWING MAY NOT BE COPIED, REPRODUCED, IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION	Customer:			Tolerance Unless otherwise specified			Scale: 1.8:1	Dim. in
	Name		Title	Dimensional: Angles:			Material: See Notes	
			Approval Date	2006	Date	Name	Title:	
				Draw.	Mar. 05	Vincent Ke	RJ45 Cat. 5e Ethernet Patch Cords	
				Appd.	Mar. 05	J. Chaudry	Industrial to Industrial	
d		Jan/08/08	Vincent ke	Norm		RoHS Compliant		
c		Jun/18/07	Vincent Ke	D-old		Drawing No.: 39K1A298		
b		May/15/07	Vincent ke			Part No.: SEE P/N ABOVE		
a		origin				Sheet 1/1		
Rev.		Changes	Date	Name	CONEC®			