




L	Cat. 5e STP AWG24 Solid Cable 	Cat. 5e UTP AWG24 Solid Cable					
	Black	Black	Blue	Red	Green	Yellow	White
2M	17-101324	17-100654	17-100684	17-100714	17-100744	17-100774	17-100804
4M	17-101334	17-100664	17-100694	17-100724	17-100754	17-100784	17-100814
5M	17-101344	17-100674	17-100704	17-100734	17-100764	17-100794	17-100824

Notes: - Special cable lengths are available please contact factory; STP: Shielded Twisted Pair, UTP: Unshielded Twisted Pair

**Notes:**

- Electrical:
  - Meets EIA/TIA-568-B.2 Cat.5e Specification
  - RJ45 Plug Operating Temperature: -40° C to +85° C
- Materials and Finish:
  - RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
  - RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-0
  - RJ45 Plug Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
  - RJ45 Modular Boot: PVC, Color: See P/N Table
  - Cable: See P/N Table
- RoHS compliant

Directive 2002/95/EC  
"RoHS"  
Compliant

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. <b>DO NOT ALTER CAD DRAWING BY HAND</b>	Customer:			Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in Meter
	Name	Title	Approval Date	Dimensional: Angles:			Material: See Notes	
				2008	Date	Name	Title: RJ45 Cat. 5e Ethernet Patch Cord	
				Draw.	Feb. 20	Vincent Ke	Standard to Standard	
				Appd.	Feb. 20	J. Chaudry	RoHS Compliant	
				Norm				
b		Dec/12/2008	Vincent ke			Drawing No.: 39K1A375		DIN A3
a	origin					Part No.: SEE P/N TABLE		Sheet 1/1
Rev.	Changes	Date	Name					