



Heyco® Liquid Tight Cordgrips Straight-Thru, PG Hubs

For Flexible Cords. For use in clearance or threaded holes.




CABLE DIA. RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS									
Min. Dia.		Max. Dia.		Black	Gray		A Clearance Hole		B Max. O.A. Length		C Thread Length		D Wrenching Nut Thk.		E Wrenching Flats	
in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	
.064	1,6	.210	5,3	3444	3445	RLTF 7	.492	12,5	1.17	29,7	.33	8,4	.20	5,1	.59	15,0
.114	2,9	.250	6,4	3207	3208	LTF 7										
.069	1,8	.187	4,7	3446	3447	RLTF 9	.599	15,2	1.30	33,0	.34	8,6	.20	5,1	.75	19,1
.181	4,6	.312	7,9	3210	3211	LTF 9										
.069	1,8	.250	6,6	3448	3449	RLTF 11	.733	18,6	1.46	37,1	.39	9,9	.20	5,1	.86	21,8
.230	5,8	.395	10,0	3213	3214	LTF 11										
.170	4,3	.450	11,9	3216	3217	* LTF 13.5	.804	20,4	1.53	38,9	.41	10,4	.20	5,1	.95	24,1
.230	5,8	.530	13,9	3219	3220	* LTF 16	.886	22,5	1.66	42,2	.45	11,4	.23	5,8	1.05	26,7
.250	6,4	.490	12,3	3454	3455	* RLTF 21	1.115	28,3	1.87	47,5	.52	13,2	.23	5,8	1.30	33,0
.450	11,4	.705	18,0	3222	3223	* LTF 21										
.590	15,0	.990	25,4	3225	3226	* LTF 29	1.470	37,3	2.23	56,6	.59	15,0	.28	7,1	1.66	42,2
.787	20,0	1.020	26,0	M3206	M3205	* RLTCG 36	1.850	47,0	2.52	64,0	.51	12,9	.32	8,1	2.09	53,1
.875	22,0	1.260	32,0	M3204	M3203	* LTCG 36										
1.230	31,2	1.560	39,6	M3212	M3209	LTCG 42	2.130	54,1	2.50	63,5	.45	11,4	.36	9,1	2.48	63,0
1.000	25,4	1.240	31,5	M3218	M3215	* RLTCG 42										
1.450	36,8	1.560	44,0	M3281	M3282	LTCG 48	2.340	59,4	2.63	66,7	.49	12,4	.42	10,7	2.75	69,9
1.160	29,5	1.560	34,3	M3283	M3284	RLTCG 48										


Standard colors black and gray.

*UL Listed

- Multiple sizes for cable diameters ranging from .064" (1,6 mm) to 1.730" (44,0 mm).
- We recommend using the fitting with the smallest maximum diameter that will fit your application.
- Acme threads on body prevent skipping and speed installation.
- All nylon construction with TPE or Buna N Sealing Gland resists salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents. This feature is not assessed by UL.
- TPE Sealing Gland is used in LTF Series.
- Buna N Sealing Gland is used in LTCG Series.
- PG hub threads are steel conduit threads per DIN 40430.
- Suitable for NEMA type 6 enclosures.
- **Locknuts INCLUDED.**
- Consult Heyco for cordgrips molded in other colors.



SUGGESTED CLEARANCE HOLE FOR NONTHEADED MOUNTING



Material	6/6 Nylon with Buna N Sealing Gland (LTCG Series) or TPE Gland (LTF Series)
Certifications	<ul style="list-style-type: none"> UL Listed under Underwriters' Laboratories File E51579 Recognized under the Component Program of Underwriters' Laboratories File E51579 CSA Certified by Canadian Standards Association File LR93876C
Flammability Rating	94V-2
Temperature Rating	Static -40°F (-40°C) to 239°F (115°C) Dynamic -4°F (-20°C) to 212°F (100°C)
IP Rating	IP 68 (70 PSI, 5 BAR)

Quick Specs