



MINISMDC030F-2 Product Details

[Share](#) | [Print](#) | [Email](#)


MINISMDC030F-2
(RF1907-000)

TE Internal Number: RF1907-000

Active

PolySwitch Resettable Devices

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Surface Mount Application
- Vmax Operating = 30 V
- Vmax = 30 V
- Imax = 40 A
- Family Name = miniSMD

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • CP CATALOG 2011 - SURFACE-MOUNT (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • miniSMDC030F (PDF, English) <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Related Products:</p> <ul style="list-style-type: none"> • Tooling
--	---

[List all Documents](#)

Feedback

Product Features (Please use the Product Drawing for all design activity)

<p>Product Type Features:</p> <ul style="list-style-type: none"> • Family Name = miniSMD • CSA File Number = CA78165 <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Vmax Operating (V) = 30 • Vmax (V) = 30 • Imax (A) = 40 • IH (Room Temperature) (A) = 0.3 • IT (Room Temperature) (A) = 0.60 • Rmin (Ω) = 0.20 • R1 Max [Post Trip] (Ω) = 1.75 • Power Dissipation (Max) (W) = 0.8 <p>Termination Features:</p> <ul style="list-style-type: none"> • Construction = Surface Mount <p>Configuration Features:</p> <ul style="list-style-type: none"> • Form Factor (inches) = 1812 • Form Factor (mm) = 4532 	<p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C • RoHS/ELV Compliance History = Always was RoHS compliant • UL File Number = E74889 <p>Environmental:</p> <ul style="list-style-type: none"> • Operating Temperature (Max.) (°C) = 85 <p>Operation/Application:</p> <ul style="list-style-type: none"> • Application = Surface Mount <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Tape & Reel <p>Other:</p> <ul style="list-style-type: none"> • Brand = Raychem
---	---

