











SIGNAL SWITCHING RELAYS

Relay Type	P2	D2n	TSC	W11	Cradles
					
					
Contacts					
Configuration	2 C/O	2 C/O	1 C/O	1 C/O	2 C/O, 4 C/O, 6 C/O
Rated Current	2 Amps	3 Amps	1 Amp	3 Amps	0.2 - 5 Amps
Rated Voltage	220Vdc, 250Vac	250Vdc, 230Vac	30Vdc, 120Vac	60Vdc, 125Vac	36 - 250Vdc, 30 - 230Vac
Rated breaking capacity	60W, 62.5 VA	60W, 120 VA	24W, 120 VA	72W, 360 VA	5 - 140W, 5 - 500 VA
Contact material	AgNi + Au plate	AgNi + Au plate	AgNi + Au plate	AgPd / AgNi plate	Ag + Au flash
Coil					
Coil Voltage Range (dc/ac)	3 - 24 / -	3 - 48 / -	3 - 24 / -	5 - 24 / -	3 - 125 / 6 - 230
Nominal coil power (dc/dc)	70 - 140mW / -	150 - 500mW / -	150mW / -	200, 450mW / -	800mW / 1.15 VA
Other coil versions	Bistable 1 & 2 coil				Bistable
General data					
Dielectric Strength	1500 Vac	1000 Vac	1500 Vac	1000 Vac	500 - 1500 Vac
Creepage/Clearance	1.5 / 2.5				
Temperature range (°C)	-40 to +85	-25 to +60 - 85	-40 to +85	-40 to +70, +85	-40 to +70
Sealing		Washable	Washable	Washable	Dust Proof, Hermetic
Termination method	PCB, SMT	PCB	PCB	PCB	PCB, Plug-in
Dimensions mm (L x W x H)	15 x 7.5 x 9.9	20.3 x 10.1 x 11.5	12.5 x 7.5 x 10	15.6 x 10.6 x 11.5	24 - 35 x 19 x 30
Approvals (Technical data on approved types on request)	UL, CSA	UL, CSA	UL, CSA		