


Zener Diodes

Features

- Silicon planar power Zener diodes
- For use in stabilizing and clipping circuits with high power rating
- The Zener voltages are graded according to the international E 24 standard. Smaller voltage tolerances are available upon request
- These diodes are also available in the DO-41 case with the type designation ZPY3V9 to ZPY100
- AEC-Q101 qualified
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



RoHS
COMPLIANT
HALOGEN
FREE



18315

Mechanical Data

Case: MELF DO-213AB (glass)

Weight: approx. 135 mg

Cathode band color: black

Packaging codes/options:

GS18/5 k per 13" reel (12 mm tape), 10 k/box

GS08/1.5 k per 7" reel (12 mm tape), 12 k/box

Absolute Maximum Ratings

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Zener current (see Table "Characteristics")				
Power dissipation		P_{tot}	1 ¹⁾	W

Note

¹⁾ Valid provided that electrodes are kept at ambient temperature.

Thermal Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Thermal resistance junction to ambient air		R_{thJA}	170 ¹⁾	K/W
Thermal resistance junction to case		R_{thJC}	60	K/W
Junction temperature		T_j	175	$^{\circ}\text{C}$
Storage temperature		T_{stg}	- 55 to + 175	$^{\circ}\text{C}$

Note

¹⁾ Valid provided that electrodes are kept at ambient temperature.

Electrical Characteristics

Part number	Zener voltage ²⁾		Dynamic resistance		Temperature coefficient of Zener voltage		Test current	Reverse voltage	Admissible Zener current ¹⁾
	V_Z at I_{ZT}		r_{zj} at I_{ZT} , $f = 1$ kHz		α_{VZ} at I_{ZT}		I_{ZT}	V_R at $I_R = 0.5 \mu A$	I_Z at $T_{amb} = 25^\circ C$
	V		Ω		$10^{-4}/^\circ C$		mA	V	mA
	min.	max.	typ.	min.	max.				
ZMY3V9	3.7	4.1	7	4	- 7	2	100	-	203
ZMY4V3	4	4.6	7	4	- 7	3	100	-	182
ZMY4V7	4.4	5	7	4	- 7	4	100	-	165
ZMY5V1	4.8	5.4	5	2	- 6	5	100	0.7	150
ZMY5V6	5.2	6	2	1	- 3	5	100	1.5	135
ZMY6V2	5.8	6.6	2	1	- 1	6	100	2	128
ZMY6V8	6.4	7.2	2	1	0	7	100	3	110
ZMY7V5	7	7.9	2	1	0	7	100	5	100
ZMY8V2	7.7	8.7	2	1	3	8	100	6	89
ZMY9V1	8.5	9.6	4	2	3	8	50	7	82
ZMY10	9.4	10.6	4	2	5	9	50	7.5	74
ZMY11	10.4	11.6	7	3	5	10	50	8.5	66
ZMY12	11.4	12.7	7	3	5	10	50	9	60
ZMY13	12.4	14.1	9	4	5	10	50	10	55
ZMY15	13.8	15.8	9	4	5	10	50	11	49
ZMY16	15.3	17.1	10	5	7	11	25	12	44
ZMY18	16.8	19.1	11	5	7	11	25	14	40
ZMY20	18.8	21.2	12	6	7	11	25	15	36
ZMY22	20.8	23.3	13	7	7	11	25	17	34
ZMY24	22.8	25.6	14	8	7	12	25	18	29
ZMY27	25.1	28.9	15	9	7	12	25	20	27
ZMY30	28	32	20	10	7	12	25	22.5	25
ZMY33	31	35	20	11	7	12	25	25	22
ZMY36	34	38	60	25	7	12	10	27	20
ZMY39	37	41	60	30	8	12	10	29	18
ZMY43	40	46	80	35	8	13	10	32	17
ZMY47	44	50	80	40	8	13	10	35	15
ZMY51	48	54	100	45	8	13	10	38	14
ZMY56	52	60	100	50	8	13	10	42	13
ZMY62	58	66	130	60	8	13	10	47	11
ZMY68	64	72	130	65	8	13	10	51	10
ZMY75	70	79	160	70	8	13	10	56	9
ZMY82	77	88	160	80	8	13	10	61	8
ZMY91	85	96	250	120	9	13	5	68	7.5
ZMY100	94	106	250	130	9	13	5	75	7

Notes

¹⁾ Valid provided that electrodes are kept at ambient temperature

²⁾ Tested with pulses $t_p = 5$ ms

Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified




Figure 1. Dynamic Resistance vs. Zener Current




Figure 4. Admissible Power Dissipation vs. Ambient Temperature




Figure 2. Dynamic Resistance vs. Zener Current




Figure 5. Pulse Thermal Resistance vs. Pulse Duration




Figure 3. Dynamic Resistance vs. Zener Current

ZMY3V9 to ZMY100

Vishay Semiconductors




Figure 6. Breakdown Characteristics




Figure 8. Breakdown Characteristics






Figure 7. Breakdown Characteristics

Package Dimensions in millimeters (inches): MELF DO-213AB (glass)



★ The gap between plug and glass can be either on cathode or anode side

Foot print recommendation:



Document no.:S8-V-3453.02-001 (4)
 Rev. 3 - Date: 07 June 2006
 18317



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.