



Notes:

1. Electrical Specifications:

- Meets EIA/TIA-568-B.2 Cat.5e Specification
- Contact Resistance: 20mOhm max.
- Insulation Resistance: 500MOhm min. @ 100 VDC
- Current Rating: 1.2A max. at 25°C
- Working Voltage: 100 VDC
- DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
- Operating Temperature: -40°C to +85°C

2. Material and Finish:

- Receptacle Housing: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
- Cover Coupling Ring: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
- Panel Nut: Brass, Finish: Nickel Plated
- Panel Gasket: Silicone, Color: White
- Cover Gasket: Silicone, Color: Red
- Tether: Polycarbonate, Color: Black
- RJ45 IDC Jack Metal Shell: Copper Alloy, Nickel Plated
- RJ45 IDC Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
- RJ45 IDC Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel

3. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.

4. RoHS compliant

Directive 2002/95/EC
"RoHS"
Compliant

Description	Part Number
Plastic Version with Shielded RJ45 IDC Jack with Cover	17-10021
Metallized Plastic Version with Shielded RJ45 IDC Jack with Cover	17-10022
Potted Plastic Version with Shielded RJ45 IDC Jack with Cover	17-10037
Potted Metallized Plastic Version with Shielded RJ45 IDC Jack with Cover	17-10038

<small>THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION</small> DO NOT ALTER CAD DRAWING BY HAND	Customer:			<small>Tolerance Unless otherwise specified</small> 0 PLC ±0.50 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±3°		Scale: 1:2:1	Dim. in mm
	Name	Title	Approval Date			Material: See Notes	
						File:	
						Receptacle & Cover Assembly Kit	
						Industrial Ethernet Connector (IP67)	
	c	May/25/09	Vincent Ke	Draw.	Oct 25	J. Chaudry	
	b	Jan/28/08	Vincent Ke	Appd.	Oct 25		
	a	origin		Norm			
	Rev.	Changes	Date	Name			
						Drawing No.: 39K1A334	DIN A3
						Part No.: SEE P/N ABOVE	Sheet 1/1