


- △ DOUBLE BAR POLARIZATION
- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- △ POSTS: GOLD FLASH OVER PALLADIUM-NICKEL PLATE, .000030 MIN TOTAL ON THE MATING SURFACES, .000100 MIN TIN-LEAD PLATE ON THE SOLDER-TAILS, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE POST.  
-OR-  
.000030 MIN GOLD PLATE ON THE MATING SURFACES, .000100 MIN TIN-LEAD PLATE ON THE SOLDER-TAILS, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
- △ CENTER POLARIZATION SLOT
- △ FOR 10 POSN ASSEMBLY, SLOT OMITTED WHERE INDICATED
- △ OPTIONAL AMP IDENTIFICATION NUMBER (DATE CODE). LOCATION APPROXIMATELY WHERE SHOWN.
- △ PACKAGED IN GANG OF TUBES.
- △ NUMBER 1 POSITION.



△ OBSOLETE	2.800	2.400	24	50	1-103309-8
△ OBSOLETE	1.500	1.100	11	24	1-103309-7
△ OBSOLETE	1.600	1.200	12	26	1-103309-4
△ OBSOLETE	1.300	.900	9	20	1-103309-3
OBSOLETE	3.300	2.900	29	60	1-103309-2
OBSOLETE	3.100	2.700	27	56	1-103309-1
	2.800	2.400	24	50	1-103309-0
OBSOLETE	2.500	2.100	21	44	103309-9
	2.300	1.900	19	40	103309-8
	2.000	1.600	16	34	103309-7
	1.600	1.200	12	26	103309-6
	1.300	.900	9	20	103309-5
OBSOLETE	1.200	.800	8	18	103309-4
	1.100	.700	7	16	103309-3
	1.000	.600	6	14	103309-2
	.800	.400	4	10	103309-1
	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

APPROVED: H. MOLL, 8-27-87  
 CHK: L. MEYER, 9-03-87  
 NAME: R. FEIDT, 9-03-87

TE Connectivity

HEADER ASSY, LOW PROFILE, AMP-LATCH

108-40018

SIZE: A1, CAGE CODE: 00779, DRAWING NO: 103309

WEIGHT: --

CUSTOMER DRAWING

SCALE: 4:1, SHEET: 1 OF 1, REV: N1