



注) NOTE.

1. そりは長さ25.4mmに対して0.2mmMAX X. CAMBER MUST BE WITHIN 0.2 MAX. PER 25.4.
2. ( ) 寸法は参考値 DIMENSION SHOWN IN ( ) ARE REFERENCE.
3. サーキットNO. 1のみ表示 但し2極の場合は MX-Jマーク側が1となる WHEN 2 CIRCUITS HOUSING TRADE MARK SIDE IN NO.1 CIRCUIT.

CAV.NO. 型番 ENG.NO. 5051  
 TRADE MARK  
 サーキットNO. (注3参照)  
 CIRCUIT NO. (1 ONLY) SEE NOTE 3.

ターミナル#2759又は#5159  
 TERMINAL #2759 OR #5159

MT'L. NYLON 66(94V-0)

| 5051-20      | 22-01-1202 | 20   | 47.50±0.30 | 50.50            |
|--------------|------------|------|------------|------------------|
| ▲ -16        | ▲ -1162    | 16   | 37.50±0.25 | 40.50            |
| -15          | -1152      | 15   | 35.00±0.20 | 38.00            |
| -14          | -1142      | 14   | 32.50±0.20 | 35.50            |
| -13          | -1132      | 13   | 30.00±0.20 | 33.00            |
| -12          | -1122      | 12   | 27.50±0.20 | 30.50            |
| -11          | -1112      | 11   | 25.00±0.15 | 28.00            |
| -10          | -1102      | 10   | 22.50±0.15 | 25.50            |
| -09          | -1092      | 9    | 20.00±0.15 | 23.00            |
| -08          | -1082      | 8    | 17.50±0.15 | 20.50            |
| -07          | -1072      | 7    | 15.00±0.15 | 18.00            |
| -06          | -1062      | 6    | 12.50±0.10 | 15.50            |
| -05          | -1052      | 5    | 10.00±0.10 | 13.00            |
| -04          | -1042      | 4    | 7.50±0.10  | 10.50            |
| ▼ -03        | ▼ -1032    | 3    | 5.00±0.10  | 8.00             |
| 5051-02      | 22-01-1022 | 2    | 2.50±0.08  | 5.50             |
| MATERIAL NO. | PART NO.   | 極数 N | B          | (A)              |
|              |            |      |            | MODEL NO. 5051-N |

|   |                                       |   |                             |                             |  |                        |                        |  |
|---|---------------------------------------|---|-----------------------------|-----------------------------|--|------------------------|------------------------|--|
| REVISED<br>EC NO: J2009-0064<br>DRWN: MAKURAA 2008/08/01<br>CHKD: T. HARIYAMA 2008/08/01<br>APPR: NUKITA 2008/12/19 | GENERAL TOLERANCES (UNLESS SPECIFIED) |   | DIMENSION STYLE<br>MM ONLY  |                             | SCALE<br>4:1                                 | DESIGN UNITS<br>METRIC | THIRD ANGLE PROJECTION |  |
|   | 10 UNDER                              | ±0.25   | DRAWN BY<br>K. KOHAMA       | DATE<br>'00/3/28            | TITLE<br>2.50/(.098) CENTERS KK<br>POLZG HSG |                        |                        |  |
|   | 10 OVER 30 UNDER                      | ±0.3  | CHECKED BY<br>T. YAMAGUCHI  | DATE<br>'00/3/30            |  |                        |                        |  |
|   | 30 OVER                               | ±0.35   | APPROVED BY<br>M. FUKUSHIMA | DATE<br>'00/3/30            | MOLEX INCORPORATED                           |                        |                        |  |
| ANGULAR ±3 °  |                                       | MATERIAL NO.<br>SEE TABLE   |                             | DOCUMENT NO.<br>SD-5051-001 |  |                        |                        |  |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS  |                                       | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION |                             |                             |  |                        |                        |  |