

# **Material Safety Data Sheet**

Copyright, 2007, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This material safety data sheet (MSDS) is provided as a courtesy in response to a customer request. This product is not regulated under, and a MSDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M BRAND COLORED 35 AND 1700C VINYL ELECTRICAL TAPES

**MANUFACTURER:** 3M

**DIVISION:** Electrical Markets Division

**ADDRESS:** 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 01/05/2007 **Supercedes Date:** 03/14/2001

**Document Group:** 09-3522-1

**Product Use:** 

Intended Use: Reinsulating and color-coding electrical wiring

## **SECTION 2: INGREDIENTS**

| Ingredient  | C.A.S. No.   | <u>% by Wt</u> |
|---|--------------|----------------|
| POLY(VINYL CHLORIDE)  | 9002-86-2    | 48 - 54        |
| POLYESTER ADIPATE   | Trade Secret | 20 - 26        |
| DISTILLATES (PETROLEUM), C3-6, PIPERYLENE-RICH, POLYMERS WITH | 152698-66-3  | 10 - 14        |
| ISOBUTYLENE   |              |                |
| CERAMIC MATERIALS AND WARES, CHEMICALS                        | 66402-68-4   | 2 - 4          |
| ANTIMONY TRIOXIDE   | 1309-64-4    | 2 - 4          |
| EPOXIDIZED SOYBEAN OIL  | 8013-07-8    | 2 - 4          |
| DI-C8-10-BRANCHED ALKYL PHTHALATE, C9 RICH                    | 68515-48-0   | 2 - 4          |
| Misc Fillers and process aids                                 | Mixture      | 2 - 4          |

This product complies with Directive 2002/95/EC of the European Parliament on the Restriction of Hazardous Substances (RoHS)

## **SECTION 3: HAZARDS IDENTIFICATION**

## 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Roll of Tape Odor, Color, Grade: various colors General Physical Form: Solid

**Immediate health, physical, and environmental hazards:** This product, when used under reasonable conditions and in accordance with the 3M directions for use, should not present a health hazard. However, use or processing of the product in a

manner not in accordance with the product's directions for use may affect the performance of the product and may present potential

health and safety hazards.

## 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:** 

No health effects are expected.

**Skin Contact:** 

No health effects are expected.

**Inhalation:** 

No health effects are expected.

**Ingestion:** 

No health effects are expected.

## **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** No need for first aid is anticipated.

**Skin Contact:** No need for first aid is anticipated.

**Inhalation:** No need for first aid is anticipated.

**If Swallowed:** No need for first aid is anticipated.

# **SECTION 5: FIRE FIGHTING MEASURES**

## 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNo Data AvailableFlash PointNo Data AvailableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot Applicable

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** See Hazardous Decomposition section for products of combustion. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** No unusual fire or explosion hazards are anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Not applicable.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid contact with oxidizing agents.

### 7.2 STORAGE

Store away from heat. Store away from oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Not applicable.

# 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

## 8.2.1 Eye/Face Protection

Not applicable.

## 8.2.2 Skin Protection

Gloves are not required. A Material Safety Data Sheet (MSDS) is not required by the OSHA Hazard Communication Standard (29CFR 1910.1200) for this product. This MSDS is provided as a service to customers.

### **8.2.3 Respiratory Protection**

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

| <u>Ingredient</u>       | <b>Authority</b> | <b>Type</b> | <u>Limit</u> | <b>Additional Information</b> |
|-------------------------|------------------|-------------|--------------|-------------------------------|
| ANTIMONY COMPOUNDS      | ACGIH            | TWA, as Sb  | 0.5  mg/m3   |                               |
| ANTIMONY COMPOUNDS      | OSHA             | TWA, as Sb  | 0.5  mg/m3   | Table Z-1A                    |
| ANTIMONY TRIOXIDE       | ACGIH            | TWA, as Sb  | 0.5 mg/m3    |                               |
| DI-C8-10-BRANCHED ALKYL | CMRG             | TWA         | 5 mg/m3      |                               |

#### 3M MATERIAL SAFETY DATA SHEET 3M BRAND COLORED 35 AND 1700C VINYL ELECTRICAL TAPES 01/05/2007

PHTHALATE, C9 RICH

Table A4 **STEARATES ACGIH** TWA, as total dust 10 mg/m3

### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Specific Physical Form:** Roll of Tape Odor, Color, Grade: various colors Solid

**General Physical Form:** 

**Autoignition temperature** No Data Available **Flash Point** No Data Available Flammable Limits - LEL Not Applicable Flammable Limits - UEL Not Applicable Not Applicable **Boiling point** 

Vapor Density Not Applicable

Vapor Pressure Not Applicable

**Specific Gravity** 1.22

pН Not Applicable **Melting point** No Data Available

Not Applicable **Evaporation rate** <=0.1 % weight **Volatile Organic Compounds VOC Less H2O & Exempt Solvents** No Data Available Viscosity Not Applicable

# **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid: Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

# **Hazardous Decomposition or By-Products**

Substance

Hydrocarbons At Elevated Temperatures - >90 C

Carbon monoxide **During Combustion** Carbon dioxide **During Combustion** Hydrogen Chloride **During Combustion** Oxides of Antimony **During Combustion** 

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

## ECOTOXICOLOGICAL INFORMATION

Not applicable.

### CHEMICAL FATE INFORMATION

Not applicable.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in an industrial or commercial facility in the presence of a combustible material. Combustion products will include HCl. Facility must be capable of handling halogenated materials.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14:TRANSPORT INFORMATION

### **ID** Number(s):

 $80-6112-3604-5,\ 80-6112-3605-2,\ 80-6112-3606-0,\ 80-6112-3607-8,\ 80-6112-3608-6,\ 80-6112-3609-4,\ 80-6112-3610-2,\ 80-6112-3611-0,\ 80-6112-3612-8$ 

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

# **SECTION 15: REGULATORY INFORMATION**

### US FEDERAL REGULATIONS

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

IngredientC.A.S. No% by WtANTIMONY TRIOXIDE (ANTIMONY)1309-64-42 - 4

COMPOUNDS)

## STATE REGULATIONS

Contact 3M for more information.

### **CHEMICAL INVENTORIES**

The components of this product are in compliance with the chemical notification requirements of TSCA.

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

### INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

### **NFPA Hazard Classification**

Health: 0 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### **HMIS Hazard Classification**

**Health:** 0 Flammability: 0 Reactivity: 0 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

**Reason for Reissue:** The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

No revision information is available.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

| IATERIAL SAFETY DATA SHEET 3M BRAND COLORED 35 AND 1700C VINYL ELECTRICAL TAPES 01/05/2007 |        |  |  |  |
|--|--------|--|--|--|
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
| 3M MSDSs are available at www.   | 3M.com |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |
|  |        |  |  |  |