


HEYCO




Heyco® Snap-in PG Liquid Tight Bushings

- Can be used in threaded or unthreaded holes.
- Ozone and weather resistant.
- Provides light strain relief to the cable.
- Simple to install—just snap into place, pierce thin membrane, insert & pull back cable.
- Can be used as a liquid tight plug. Offers protection to IP 67.
- Sizes available to fit cable diameters ranging from .12" (3,0 mm) up to 1.38" (35,0 mm).




PANEL DIMENSIONS						CABLE DIAMETER RANGE				PART NO.	DESCRIPTION	Hole Size	PART DIMENSIONS					
Hole Diameter		Thickness Range											D	H	L			
													Head Diameter	Head Thickness	Overall Length			
in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	Gray			in.	mm.	in.	mm.	in.	mm.
.52	13,2	.04	1,0	.16	4,0	.12	3,0	.20	5,0	4014	LTB 30-50/PG7	PG7	.79	20,0	.24	6,1	.50	12,8
.63	16,0	.04	1,0	.16	4,0	.20	5,0	.28	7,0	4015	LTB 50-70/PG9	PG9	.79	20,0	.28	7,1	.75	19,0
.75	19,0	.04	1,0	.16	4,0	.28	7,0	.39	10,0	4016	LTB 70-100/PG11	PG11	.94	24,0	.28	7,1	.81	20,6
.91	23,0	.04	1,0	.16	4,0	.31	8,0	.55	14,0	4017	LTB 80-140/PG16	PG16	1.10	28,0	.28	7,1	.89	22,5
1.14	29,0	.04	1,0	.16	4,0	.55	14,0	.79	20,0	4018	LTB 140-200/PG21	PG21	1.36	34,5	.28	7,1	1.02	26,0
1.50	38,0	.04	1,0	.16	4,0	.79	20,0	1.02	26,0	4019	LTB 200-260/PG29	PG29	1.81	46,0	.26	6,6	1.14	29,0
1.89	48,0	.04	1,0	.16	4,0	1.02	26,0	1.38	35,0	4020	LTB 260-350/PG36	PG36	2.26	57,5	.31	7,9	1.42	36,0


Standard color gray.



Snap Into Panel




Pierce and Insert Cable



Pull Back Cable to Form Seal

Heyco® Snap-In Metric Liquid Tight Bushings

- For outdoor and indoor applications
- Good weather, UV, and ozone resistance



PANEL DIMENSIONS						CABLE DIA. RANGE				PART NO.	DESCRIPTION	PART DIMENSIONS							
Hole Diameter		Thickness Range				Min.		Max.				Gray	D Head Diameter		H Body Thickness		L Overall Length		Hole Size
in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.	
.49	12,5	.02	0,5	.08	2,0	.16	4,0	.28	7,0	4007	LTB 30-50/M12	.79	20,0	.22	5,6	.50	12,8		
.65	16,5	.04	1,0	.16	4,0	.20	5,0	.35	9,0	4008	LTB 50-70/M16	.83	21,0	.46	11,6	.70	17,7		
.81	20,5	.04	1,0	.16	4,0	.32	8,0	.51	13,0	4009	LTB 70-100/M20	1.00	25,5	.53	13,4	.79	20,0		
1.00	25,5	.04	1,0	.16	4,0	.43	11,0	.67	17,0	4010	LTB 100-140/M25	1.20	30,5	.60	15,3	.84	21,3		
1.28	32,5	.04	1,0	.16	4,0	.59	15,0	.79	20,0	4011	LTB 140-200/M32	1.52	38,5	.73	18,6	.97	24,6		
1.59	40,5	.04	1,0	.16	4,0	.75	19,0	1.10	28,0	4012	LTB 200-260/M40	1.91	48,5	.85	21,7	1.16	29,5		
1.99	50,5	.04	1,0	.16	4,0	1.06	27,0	1.38	35,0	4013	LTB 260-350/M50	2.38	60,5	.98	25,0	1.37	34,8		

Standard color gray.

Quick Specs

Material
Temperature Rating
IP Rating

Ethylene Propylene Diene Monomes Rubber (EPDM)
-40°F (40°C) to 200°F (93°C)
IP 67



Heyco® Polyurethane Adhesive Backed Bumpers

Hemispherical

- Bumpers can be attached to a wide variety of surfaces; aluminum, ceramic, formica, glass, painted surfaces, polyethylene, polypropylene, vinyl, and steel.
- Quick and easy installation—simply peel off backing and press into place. With no holes to drill, and no screws or rivets needed, adhesive backed bumpers will save you time and money.
- Adhesive backed bumpers are nonmarking, nonstaining, skid, and scratch resistant.
- Surface must be clean, dry, and free of grease, oil, and other common solvents to obtain maximum adhesion. Clean surfaces with low strength solvents such as Isopropyl Alcohol or Heptane.
- Recommended storage guidelines: temperature range 40°F (40°C) to 75°F (24°C), humidity range 40% to 60%.
- Bumpers have a rubber-based pressure sensitive adhesive with an end use temperature of 0°F (-18°C) to 180°F (82°C).

PART NO.	DESCRIPTION	PART SPECIFICATIONS/DIMENSIONS				
		A		B		Pieces per Pad
		Diameter		Height		
Black		in.	mm.	in.	mm.	
N140	HBA 250-06	.25	6,4	.06	1,6	578
N107	HBA 335-09	.34	8,6	.09	2,3	450
N112	HBA 375-15	.38	9,7	.15	3,8	200
N102	HBA 440-20	.44	11,2	.20	5,1	242
N115	HBA 620-31	.62	15,7	.31	7,9	128
N108	HBA 700-38	.70	17,8	.38	9,7	98
N139	HBA 750-08	.75	19,1	.08	2,0	84

 Recognized under the Component Program of Underwriters' Laboratories File E196663.

