



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BRASS PER QQ-B-613
3. NICKEL PL 100 MIN. THICK OVER COPPER STRIKE
4. PHOSPHOR BRONZE PER QQ-B-750
5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
6. TEFLON MIL-P-19468
7. JIS H 3250, C 2700

ACCEPTS ø0.75~0.9 CENTER CONDUCTOR TYPICAL

1. CRIMPED FERRULE  
HEX CRIMP SIZE .255"
2. CRIMPED CONTACT PIN  
SQ. CRIMP SIZE .052"
3. MAX. PANEL THICKNESS=6.5mm

6	HEX NUT	NOTE 1	NOTE 3	1	HN127-3/8-32X3	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	PART NO. F6411A2-NT3G-3-75		<b>Amphenol</b>	
5	LOCK WASHER	NOTE 2	NOTE 3	1	LW-127/97X05		APPROVED	DATE 10-11-01'		TITLE F BULKHEAD CRIMP JACK
4	FERRULE	NOTE 7	NOTE 3	1	FR-75/66X127		CHECKED	DATE 10-11-01'		DRAWING NO. KJ-F6411A2-NT3G-59U-75
3	CONTACT PIN	NOTE 4	NOTE 5	1	F6411B3-3-16/076		DRAWN	DATE 10-11-01'		ITEM NO.
2	INSULATOR	NOTE 6	NATURAL	1	F6411B3-2		SCALE 2.5/1 ISSUE A			
1	BODY	NOTE 1	NOTE 3	1	F6411A2-1-56/39					
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	ISSUE	FILE NO.		

1 2 3 4 5 6 7 8