





- Notes
- ① The recommended clamp torque of REF. No. ① to be 3 to 3.5 N·m.
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent
REF. No. ① from loosening.
 - ② The recommended clamp torque of REF. No. ④ to be 0.65 to 0.7 N·m.
 - ③ Sealing and airtightness and oil resisting shall be tested
under mated condition with an applicable connector.

| | | | | | | | | |
|---|---|----------------------|---|---------------|--------------------------------|--|---------|------|
| 2 | POLYPHENYLENE SULFIDE | (BLACK) | UL94V-0 | 4 | STAINLESS STEEL | M3×0.5×8 | | |
| 1 | BRASS | BLACK CHROME PLATING | | 3 | ACRYLONITRILE BUTADIENE RUBBER | (GRAY) | | |
| NO. | MATERIAL | FINISH . REMARKS | | NO. | MATERIAL | FINISH . REMARKS | | |
| UNITS mm |  | SCALE 2 : 1 |  | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|  HIROSE ELECTRIC CO., LTD. | | APPROVED | | HY. KOBAYASHI | 15.08.05 | DRAWING NO. EDC-110603-71-00 | | |
| | | CHECKED | | HY. KOBAYASHI | 15.08.05 | PART NO. JR16WCC-10(71) | | |
| | | DESIGNED | | HY. KISHI | 15.08.05 | CODE NO. CL114-2055-4-71 | | |
| | | DRAWN | | HY. KISHI | 15.08.05 |  1/ | | |