



Seiko Instruments

Thermal Printer Division


# CAP9000 series and LTP9000 series 24V **Print** Mechanisms

## CAP9000 Series and LTP9000 series


Outdoor printing applications demand rugged technology for unforgiving environments. The innovative CAP9000 series and LTP9000 series (without cutter) answer this challenge with best-in-class, durable, high-performance, compact designs, supporting 2" and 3" print widths. These dynamic 24-volt mechanisms are ideal for self-service applications including kiosks and ATMs where space is at a premium and reliability is a must. Curved and straight paper path options provide added design flexibility. And, they can accommodate very large paper rolls and a range of paper thicknesses, from receipts to tickets.




- High speed printing (up to 250 mm/sec)
- Rugged design (min. 150 km print life)
- Small footprint
- Extreme temperature support (-20° to 60°C)
- Ideal for self-service applications




CAP9247




CAP9347



IF9001-01P



IF9001-01S



IF9001-01U



Seiko Instruments USA Inc.  
Thermal Printer Division  
2990 Lomita Blvd., Torrance, CA 90505  
Telephone (310) 517-7778  
Facsimile (310) 517-8154  
Email: [printerinfo@siu-la.com](mailto:printerinfo@siu-la.com)  
[www.siiprinters.com](http://www.siiprinters.com)

# CAP 9000 series 24V **Print** Mechanisms

## Product Specifications

Model	CAP9247	CAP9347	LTP9247	LTP9347
	Thermal line dot printing			
	Method			
	Number of dots/line			
	Resolution(dots/mm)			
Printing	Paper width (mm)			
	Printing width (mm)			
	Speed (max mm/sec)			
	Paper path			
	Head temperature			
Sensors	Out of paper detection			
	Mark position detection			
	Platen position detection			
	Cutter position detection			
Power supply (V)	Operating Voltage (Vdd)			
	Operating Voltage (Vp)			
Peak current (A)	Head			
	Motor			
Cutting	Method			
	Paper thickness (μm)			
	Cutting type			
	Operating time (max sec/cycle)			
	Cutting pitch (min mm)			
	Cut frequency (max cuts/min)			
	Pulse activation			
Service life	Abrasion resistance (km)			
	Auto-cutter (cuts)			
	Operating temperature (°C)			
Dimensions (W x D x H mm)				
Mass(g)				

\*Use recommended thermal papers \*\*Excluding protrusion

## Interface Board

Model	IF9001-01U	IF9001-01S	IF9001-01P
CPU	IF9001 only		
Thermal printer	CAP9247, CAP9347		
Operating voltage (V)	Vp: 21.6 to 26.4		
Character matrix (H x W dots)			
Optional font			
Downloaded character			
Character type	User-defined character		
	Extend graphics character set		
	Katakana character set		
	JIS 1&2 level kanji		
Interface	USB	Serial (RS-232C)	Parallel
Dimensions (W x D x H mm)			