

To our customers,

Old Company Name in Catalogs and Other Documents

On April 1st, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: <http://www.renesas.com>

April 1st, 2010
Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (<http://www.renesas.com>)

Send any inquiries to <http://www.renesas.com/inquiry>.

Notice

1. All information included in this document is current as of the date this document is issued. Such information, however, is subject to change without any prior notice. Before purchasing or using any Renesas Electronics products listed herein, please confirm the latest product information with a Renesas Electronics sales office. Also, please pay regular and careful attention to additional and different information to be disclosed by Renesas Electronics such as that disclosed through our website.
2. Renesas Electronics does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Renesas Electronics products or technical information described in this document. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
3. You should not alter, modify, copy, or otherwise misappropriate any Renesas Electronics product, whether in whole or in part.
4. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation of these circuits, software, and information in the design of your equipment. Renesas Electronics assumes no responsibility for any losses incurred by you or third parties arising from the use of these circuits, software, or information.
5. When exporting the products or technology described in this document, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You should not use Renesas Electronics products or the technology described in this document for any purpose relating to military applications or use by the military, including but not limited to the development of weapons of mass destruction. Renesas Electronics products and technology may not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations.
6. Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.
7. Renesas Electronics products are classified according to the following three quality grades: “Standard”, “High Quality”, and “Specific”. The recommended applications for each Renesas Electronics product depends on the product’s quality grade, as indicated below. You must check the quality grade of each Renesas Electronics product before using it in a particular application. You may not use any Renesas Electronics product for any application categorized as “Specific” without the prior written consent of Renesas Electronics. Further, you may not use any Renesas Electronics product for any application for which it is not intended without the prior written consent of Renesas Electronics. Renesas Electronics shall not be in any way liable for any damages or losses incurred by you or third parties arising from the use of any Renesas Electronics product for an application categorized as “Specific” or for which the product is not intended where you have failed to obtain the prior written consent of Renesas Electronics. The quality grade of each Renesas Electronics product is “Standard” unless otherwise expressly specified in a Renesas Electronics data sheets or data books, etc.
 - “Standard”: Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; and industrial robots.
 - “High Quality”: Transportation equipment (automobiles, trains, ships, etc.); traffic control systems; anti-disaster systems; anti-crime systems; safety equipment; and medical equipment not specifically designed for life support.
 - “Specific”: Aircraft; aerospace equipment; submersible repeaters; nuclear reactor control systems; medical equipment or systems for life support (e.g. artificial life support devices or systems), surgical implantations, or healthcare intervention (e.g. excision, etc.), and any other applications or purposes that pose a direct threat to human life.
8. You should use the Renesas Electronics products described in this document within the range specified by Renesas Electronics, especially with respect to the maximum rating, operating supply voltage range, movement power voltage range, heat radiation characteristics, installation and other product characteristics. Renesas Electronics shall have no liability for malfunctions or damages arising out of the use of Renesas Electronics products beyond such specified ranges.
9. Although Renesas Electronics endeavors to improve the quality and reliability of its products, semiconductor products have specific characteristics such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Further, Renesas Electronics products are not subject to radiation resistance design. Please be sure to implement safety measures to guard them against the possibility of physical injury, and injury or damage caused by fire in the event of the failure of a Renesas Electronics product, such as safety design for hardware and software including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult, please evaluate the safety of the final products or system manufactured by you.
10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. Please use Renesas Electronics products in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. Renesas Electronics assumes no liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
11. This document may not be reproduced or duplicated, in any form, in whole or in part, without prior written consent of Renesas Electronics.
12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products, or if you have any other inquiries.

(Note 1) “Renesas Electronics” as used in this document means Renesas Electronics Corporation and also includes its majority-owned subsidiaries.

(Note 2) “Renesas Electronics product(s)” means any product developed or manufactured by or for Renesas Electronics.

M16C/Tiny – Low-cost, Low-power-consumption, Large peripheral set

M16C/26A



Description

The M16C/Tiny Series with a wide range of memory and package types is subdivided into the M16C/26A, M16C/28 and M16C/29 device groups. These application optimised general purpose MCUs combine small foot print with high CPU performance, thus providing an excellent solution for cost sensitive applications in home appliances and industrial applications. The M16C/Tiny Series is an ideal fit for home appliances and industrial applications, which require high computing power in a small package.

With six different Flash and Mask Type MCUs available the M16C/26A is an ideal solution for a powerful flexible 16-bit design with a line-up of 42-pin SSOP and 48-pin LQFP packages with up to 64KB Flash, making it especially suitable for any motor control application.


M16C/26A provides a high level of performance, combined with internal peripherals, which reduces the need for external components. The M16C core has been designed to take advantage of the best features of both accumulator and register based architectures. The CPU has a total of thirteen 16-bit registers, seven of which come in two sets of register banks. The architecture makes it fast with efficient code execution. A hardware multiplier circuit and two direct memory access controller channels (DMAC) are implemented to speed up the processing. The M16C platform utilizes several design techniques aimed at providing excellent EMI/EMS performance without the need for external components, making it the best solution for effective designs for electrically noisy environments. Using the M16C Platform makes the CE marking for your end product to an easy task.

Key Features:

- High CPU performance 20MHz/24MHz@ 5V and 3V
- Up to 64KB Flash with 2KB RAM
- 4KB embedded VirtualEEPROM
- Two DMA channels
- 8ch 16-bit Timer
- Three Phase Motor control unit
- PLL, Main-, Sub- and On-chip oscillator
- Up to three serial ports USART including IIC
- 12ch 10-bit ADC (two S/H circuits)
- Up to 39 available I/O pins
- High efficient M16C family low power modes
- Best EMI/EMS performance

Group	Device	Package Type	Memory Type	Memory Size	
				ROM + VEE	RAM
M16C/26A	M30263F3AFP	42-pin 450mil SSOP 0.8mm pitch	Flash	24K + 4K	1K
	M30263F6AFP			48K + 4K	2K
	M30263F8AFP			64K + 4K	2K
	M30263M3A-xxxFP		Mask	24K	1K
	M30263M6A-xxxFP			48K	2K
	M30263M8A-xxxFP			64K	2K
	M30260F3AGP	48-pin 7x7mm LQFP 0.5mm pitch	Flash	24K + 4K	1K
	M30260F6AGP			48K + 4K	2K
	M30260F8AGP			64K + 4K	2K
	M30260M3A-xxxGP		Mask	24K	1K
	M30260M6A-xxxGP			48K	2K
	M30260M8A-xxxGP			64K	2K

M16C/26A – 48-pin Block Diagram



M16C CPU Core (16-bit)

- 20MHz/24MHz @ 3V and 5V, Single chip mode

Clock generation circuit

- Main clock with Xin/Xout
- Sub clock with Xcin/Xcout
- On-chip oscillator 500KHz, 1 or 8MHz
- PLL frequency synthesizer
- Main clock stop/Re-oscillation detection

Pin count	42-pin	48-pin
Peripherals		
• Timers		
– Timer A 16-bit	5ch	5ch
– Timer B 16-bit	3ch	3ch
– Three-phase motor control	1ch	1ch
• Serial I/O		
– USART	1ch	2ch
– USART, I ² C, IEBus	1ch	1ch
• DMA		
	2ch	2ch
• Watchdog Timer		
	1ch	1ch
• A/D Converter (10-bit)		
	10ch	12ch
• I/O ports		
	33-pins	39-pins
• Interrupts (7 priority levels)		
– Internal sources	18	20
– External sources	8	8
– Software sources	4	4
• CRC (CRC-CCITT or CRC-16)		
	1ch	1ch

M16C/26A Development Tools



M16C/26A Starter Kit (RSK)

The kit includes:

- CPU board with target microcontroller M16C/26A
- LCD panel for user/diagnostic interaction
- E8 on-chip debugger
- Trial C compiler and IDE
- Tutorial session
- Sample peripheral driver code
- (Part: R0K33026AS000BE)

E8 On-chip Debugger (OCD)

- Low cost OCD
- (Part: R0E000080KCE00)

Compact Emulator

- Low cost emulator with limited trace and breakpoint
- (Part: M30263T2-CPE-FP for 42-pin package)
- (Part: M30260T2-CPE-GP for 48-pin package)

Full Specification Emulator

- Full Trace, breakpoint and performance analysis
- (Part: PC7501 + M30263T-EPB-FP for 42-pin package)
- (Part: PC7501 + M30260T-EPB-GP for 48-pin package)

Compiler

- Renesas Embedded Workbench HEW4.0, C-Compiler
- IAR
- Tasking
- GNU

Greater functionality
Stronger performance

Rich range
variation within the groups.

M32C/100

M32C/90

M32C/80

M16C/60

M16C/Tiny

R8C/Tiny

Slimmer functions
Fewer pins