# **EMC Components** Common Type Chip Beads

### SMD

MCZ Series MCZ1210 Type 3 lines

Size: JIS/IEC 1210, EIA 0504

This is a common type bead product that removes the noise components in a signal line and includes beads for three lines in a single chip. The product exhibits substantial impedance characteristics in the high frequency range and is therefore capable of effectively removing differential mode noises.

Additionally, an appropriate amount of magnetic coupling is created between the beads of the three lines, giving the product the capability to remove not only differential mode noise but common mode noise as well. It is encased in a 1210 casing. This is an SMD product that allows for automatic mounting by taping.

#### FEATURES

- · Compact size and for three lines
- Capable of removing both common and differential mode noises.
- Closed magnetic circuit structure allows high-density installation while preventing crosstalk between circuits.


#### APPLICATIONS

Audio signal lines used in cell phones and mobile audio devices.

#### **TEMPERATURE RANGES**

Operating/Storage	–40 to +85°C	

# SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN



#### **ELECTRICAL CHARACTERISTICS**

MCZ	1210	С	Т	201	Т
(1)	(2)	(3)	(4)	(5)	(6)

- (1) Series name
- (2) Dimensions L×W
- (3) Material code
- (4) Number of line
- (5) Impedance
- 201: 200Ω at 100MHz
- (6) Packaging style T:Taping

#### **CIRCUIT DIAGRAM**



No polarity

#### PACKAGING STYLE AND QUANTITIES

Packaging style	Quantity
Taping	4000 pieces/reel

Part No.	Open mode impedance (Ω)[at 100MHz]	DC resistance (Ω)max.	Insulation resistance (MΩ)min.	Rated voltage (V)max.	Rated current (mA)max.	Thickness T (mm)
MCZ1210CT121T	120±25%	0.6	1	5	100	0.5
MCZ1210CT201T	200±25%	0.8	1	5	100	0.5

• Please contact our Sales office when your application are considered the following:


The device's failure or malfunction may directly endanger human life (e.g. application for automobile/aircraft/medical/nuclear power devices, etc.)

• All specifications are subject to change without notice.


# **EMC** Components

Common Type Chip Beads SMD

### **TYPICAL ELECTRICAL CHARACTERISTICS** IMPEDANCE vs. FREQUENCY CHARACTERISTICS MCZ1210CT121T



#### **MEASURING CIRCUITS**



## MCZ Series MCZ1210 Type 3 lines

Size: JIS/IEC 1210, EIA 0504

### MCZ1210CT201T

