



DRG No. <b>CP32526</b>	ISSUE <b>1</b>	TYPE No. OXL/CLH/100/-/AC/-/-		DIM. IN: MILLIMETRES	ODC:QS:40077 ISSUE 1 DO NOT SCALE	THIS DRAWING AND THE COPYRIGHT AND DESIGN RIGHT THEREIN ARE THE PROPERTY OF OXLEY DEVELOPMENTS CO. Ltd. AND MUST NOT BE REPRODUCED OR DISCLOSED TO A THIRD PARTY WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY.	ISS	MODIFICATION	DATE



MATERIALS AND FINISHES	
DESCRIPTION	MATERIAL, FINISH
BODY	BRASS BS2874 CZ121. BLACK CHROMED
LENS	POLYCARBONATE
TERMINATIONS	FLYING LEADS
NUT	ALUMINIUM ALLOY
WASHER	BeCu. TIN PLATED

OPERATING AND STORAGE TEMPERATURE : -40°C to 85°C

ELECTRICAL CHARACTERISTICS											
		AlGaAs RED		WHITE		BLUE		YELLOW		GREEN	
	UNITS	DC	AC	DC	AC	DC	AC	DC	AC	DC	AC
FORWARD CURRENT (TYP)	mA	15	7.5	15	7.5	15	7.5	15	7.5	15	7.5
LUMINOUS INTENSITY (TYP)	mcd at RATED VOLTAGE	900	450	750	375	900	450	750	375	940	470
REVERSE VOLTAGE (MAX)	V	RATED VOLTAGE									

MOUNTING DETAILS
MOUNTING HOLE : $\phi 10.15 \pm 0.1$
RECOMMENDED MOUNTING TORQUE : 1Nm
CHASSIS THICKNESS : 1.5mm (Min)

MATERIAL AS STATED	DRAWN <i>Simon Russam</i>
FINISH AS STATED	CHECKED <b>T. DAVIS</b>
PLATING AS STATED	APPROVED DA01/322
TOLERANCE AS STATED	DATE 2 APR 01

WHEN ORDERING, PLEASE STATE TYPE NUMBER, SPECIFYING FLYING LEAD LENGTH, OPERATING VOLTAGE, LED COLOUR & DC OPERATION VARIANT (IF REQUIRED)

STANDARD AC OPERATION e.g. OXL/CLH/100/12/AC/FL20/BLUE

OPERATING VOLTAGE REQUIRED (5, 12, 15, 24 or 28V)

REVERSE BLOCK DIODE PROVIDING 1/2 WAVE RECTIFICATION

FLYING LEAD LENGTH IN cm

LED COLOUR REQUIRED (AlGaAs RED, YELLOW, GREEN, BLUE or WHITE)

DC OPERATION VARIANT e.g. OXL/CLH/100/12/FL20/BLUE

OPERATING VOLTAGE REQUIRED (5, 12, 15, 24 or 28V)

FLYING LEAD LENGTH IN cm

LED COLOUR REQUIRED (AlGaAs RED, YELLOW, GREEN, BLUE or WHITE)

REMARKS

TITLE

LOW PROFILE HIGH INTENSITY LED INDICATOR LAMP



Tel. 01229 582621  
Fax. 01229 585090

**OXLEY DEVELOPMENTS COMPANY LTD.**

Ulverston  
Cumbria LA12 9QG  
ENGLAND

SCALE  
2 : 1

TYPE No.  
OXL/CLH/100/-/AC/-/-

DRG No.  
**CP32526**

ISSUE  
**1**