


## High Precision Wraparound Thin Film Chip Resistors



For low noise and precision applications, superior stability, low temperature coefficient of resistance, and low voltage coefficient, VISHAY SFERNICE's proven precision thin film wraparound resistors exceed requirements of MIL-PRF-55342G characteristics Y ( $\pm 10$  ppm/ $^{\circ}$ C).

### DIMENSIONS in millimeters (inches)



### FEATURES

- Load Life Stability at  $\pm 70$   $^{\circ}$ C for 2000 hours: 0.1 % under Pn/0.05 % under Pd
- Low Temperature Coefficient down to  $\pm 10$  ppm/ $^{\circ}$ C
- Very Low Noise < 35 dB and Voltage Coefficient < 0.01 ppm/V
- Resistance Range: 10  $\Omega$  to 3 M $\Omega$  depending on size
- Extended Ohmic Value Range (see table)
- Tolerances to  $\pm 0.01$  %
- In Lot Tracking  $\leq 5$  ppm/ $^{\circ}$ C
- Termination: Thin Film Technology
- Gold Plated or Pre-tinned Terminations over Nickel Barrier
- Short Circuits (Jumpers)  $r < 50$  mR,  $l < 2$  A



RoHS\*  
COMPLIANT

CASE SIZE	DIMENSION				POWER RATING mW		LIMITING ELEMENT VOLTAGE V	RESISTANCE RANGE (SEE BELOW FOR EXTENDED $\Omega$ RANGE)
	A	B	C	D/E				
	MAX. TOL. + 0.152 (0.006) MIN. TOL. - 0.152 (- 0.006)	MAX. TOL. + 0.127 (0.005) MIN. TOL. - 0.127 (- 0.005)	MAX. TOL. + 0.127 (0.005) MIN. TOL. - 0.127 (- 0.005)	MAX. TOL. + 0.13 (0.005) MIN. TOL. - 0.13 (- 0.005)	Pn	Pd		
0402	1.00 (0.040)	0.60 (0.023)	0.5 (0.02)	0.38 (0.015)	50	37	37	10 $\Omega$ to 50 k $\Omega$
0505	1.35 (0.053)	1.27 (0.050)	0.5 (0.02)	0.38 (0.015)	125	50	50	10 $\Omega$ to 260 k $\Omega$
0603	1.52 (0.060)	0.75 (0.030)	0.5 (0.02)	0.38 (0.015)	125	75	50	10 $\Omega$ to 260 k $\Omega$
0705 0805	1.91 (0.075)	1.27 (0.050)	0.5 (0.02)	0.38 (0.015)	200	100	50	10 $\Omega$ to 300 k $\Omega$
1005	2.54 (0.100)	1.27 (0.050)	0.5 (0.02)	0.38 (0.015)	250	125	75	10 $\Omega$ to 500 k $\Omega$
1206	3.06 (0.120)	1.60 (0.063)	0.5 (0.02)	0.38 (0.015)	330	150	75	10 $\Omega$ to 1 M $\Omega$
1505	3.81 (0.150)	1.32 (0.054)	0.5 (0.02)	0.38 (0.015)	350	175	75	10 $\Omega$ to 500 k $\Omega$
2010	5.08 (0.200)	2.54 (0.100)	0.5 (0.02)	0.38 (0.015)	1000	500	100	10 $\Omega$ to 3 M $\Omega$

EXTENDED OHMIC VALUE RANGE FOR HIGH PRECISION WRAPAROUND THIN FILM CHIP RESISTORS			
SIZE	TIGHTEST TOLERANCE %	EXTENDED OHMIC VALUE RANGE	BEST TCR (ppm/ $^{\circ}$ C)
0402	0.05	50 k - 100 k	25
	0.1	100 k - 1 M	50
0505	0.05	250 k - 300 k	25
0603	0.1	300 k - 2 M5	50
0705	0.05	300 k - 500 k	25
0805	0.1	500 k - 5 M	50
1206	0.05	1 M - 2 M	25
	0.1	2 M - 15 M	50
2010	0.05	3 M - 6 M	25
	0.25	6 M - 50 M	50

Using special NiCr and CrSi alloys we are able to extend the ohmic value range as indicated above.

\* Pb containing terminations are not RoHS compliant, exemptions may apply



**ELECTRICAL SPECIFICATIONS**

**Resistance Range:** 10 Ω to 3 MΩ  
**Resistance Tolerance:** ± 0.1 % to ± 5 %  
 ± 0.01 % to ± 0.05 % on Y type  
**Power Dissipation:** Pn: 50 mW to 1 W  
 Pd: 37 mW to 500 mW  
 on tolerance tighter than ± 0.05 %  
**Temperature Coefficient:** see table below


**MECHANICAL SPECIFICATIONS**

**Substrate:** Alumina  
**Technology:** Thin Film  
**Film:** Nickel Chromium with mineral passivation or Ta<sub>2</sub>N  
**Protection:** Silicon  
**Terminations:** **B type:** SnPb over nickel barrier for solder reflow  
**N type:** SnAg over nickel barrier  
**G type:** gold over nickel barrier for other applications

**CLIMATIC SPECIFICATIONS**

**Operating Temp. Range:** - 55 °C to + 155 °C  
 For temperature up to 200 °C, please consult factory

**POWER DERATING CURVE**



**PACKAGING**

Several types of packaging are available: tube, waffle-pack, and tape and reel.

SIZE	NUMBER OF PIECES PER PACKAGE			TAPE WIDTH	
	TUBE	WAFFLE PACK 2" x 2"	TAPE AND REEL		
			MIN.		MAX.
0402	500	100	100	4000	8 mm
0505					
0603					
0805 0705					
1005	500	140			
1206					
1505					
2010	100	60	100	2000	8 mm*

\* 12 mm on request

TEMPERATURE COEFFICIENT		
TCR	CODE	FILM
± 10 ppm/°C*	Y	Ni Cr
± 25 ppm/°C	E	Ni Cr
± 50 ppm/°C	H	Ni Cr or Ta <sub>2</sub> N
± 100 ppm/°C	K	Ni Cr or Ta <sub>2</sub> N

\* R > 50 Ω on request for lower values

BEST TOL. AND TCR V RESISTANCE VALUE			
TIGHTEST TOLERANCE	CODE	OHMIC VALUES	TCR ppm/°C
± 0.25 %	C	R > 10 Ω	± 25
± 0.10 %	B	R > 25 Ω	± 20
± 0.05 %	W	R > 50 Ω	± 10
± 0.02 %	P	R > 100 Ω	
± 0.01 %	L	R > 250 Ω	

PERFORMANCE					
TESTS	CONDITIONS	Ta <sub>2</sub> N		Ni Cr	
		MIL-PRF-55342G Requirements	Typical Performances	MIL-PRF-55342G	Typical Performances
Thermal Shock	MIL-PRF-55342G MIL-STD-202 F-Method 107 F	± 0.25 %	± 0.02 %	± 0.05 %	± 0.02 %
Short Time Overload	MIL-PRF-55342G Para 3.10.4.7.5	± 0.10 %	± 0.01 %	± 0.05 %	± 0.01 %
Low Temperature Operation	MIL-PRF-55342G Para 3.9 & 4.7.4	± 0.25 %	± 0.01 %	± 0.05 %	± 0.01 %
Resistance to Solder Heat	MIL-PRF-55342G Para 3.12, 4.7.7, 4.7.1.2	± 0.25 %	± 0.04 %	± 0.05 %	± 0.03 %
Moisture Resistance	MIL-PRF-55342G Para 3.13 & 4.7.8 MIL-STD-202 F-Method 106 E	± 0.40 %	± 0.01 %	± 0.10 %	± 0.01 %
High Temperature	MIL-PRF-55342G Para 3.11 & 4.7.6	± 0.20 %	± 0.075 %	± 0.05 %	± 0.05 %
Load Life	MIL-PRF-55342G 2000 hours Pn at 70 °C MIL-STD-202 F-Method 108 A	± 0.50 %	± 0.15 %	± 0.5 %	± 0.10 %*

\* 0.05 % under Pd

GLOBAL PART NUMBER INFORMATION																
New Global Part Numbering: P0505Y1003BBT0933																
P	0	5	0	5	Y	1	0	0	3	B	B	T	0	9	3	3
GLOBAL MODEL	SIZE		TCR		VALUE			TOLERANCE		TERMINATION		TAPE		OPTION		
P	0402 0505 0603 0705 0805 1005 1206 1505 2010		K = ± 100 ppm/°C H = ± 50 ppm/°C E = ± 25 ppm/°C Y = ± 10 ppm/°C X = Jumper Z = ± 5 ppm (0.70 °C)		The first three digits (2 digits are enough for tolerance G and J) are significant figures and the last digit specifies the number of zeros to follow, R designates decimal point  10R0 = 10 Ω 3901 = 3900 Ω 1004 = 1 MΩ 0R00 = Jumper			L = ± 0.01 % P = ± 0.02 % W = ± 0.05 % B = ± 0.1 % C = ± 0.25 % D = ± 0.5 % F = ± 1 % G = ± 2 % J = ± 5 % S = Special X = Jumper		B: SnPb over nickel barrier N: SnAg over nickel barrier G: Gold over nickel barrier  B: Lead bearing version N and G: Lead (Pb)-free/RoHS version				Leave blank if no option		
Historical Part Number example: P 0505 Y 1003 B B TR R0933 e2																
P	0505	Y		1003			B		B		TR		R0933		e2	
HISTORICAL MODEL	SIZE	TCR		VALUE			TOLERANCE		TERMINATION		TAPE		OPTION		RoHS	
P	0402 0505 0603 0705 0805 1005 1206 1505 2010	K = ± 100 ppm/°C H = ± 50 ppm/°C E = ± 25 ppm/°C Y = ± 10 ppm/°C X = Jumper Z = ± 5 ppm (0.70 °C)		The first three digits (2 digits are enough for tolerance G and J) are significant figures and the last digit specifies the number of zeros to follow, R designates decimal point  10R0 = 10 Ω 3901 = 3900 Ω 1004 = 1 MΩ 0R00 = Jumper			L = ± 0.01 % P = ± 0.02 % W = ± 0.05 % B = ± 0.1 % C = ± 0.25 % D = ± 0.5 % F = ± 1 % G = ± 2 % J = ± 5 % S = Special X = Jumper		B: SnPb over nickel barrier N: SnAg over nickel barrier G: Gold over nickel barrier  B: Lead bearing version N and G: Lead (Pb)-free/RoHS version				Leave blank if no option		e2: tin/silver e4: gold blank: SnPb	

Chips ready to be trimmed available. (P<sub>trim</sub>) - Please consult Sfernice.



## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.