

SOD323 SILICON HIGH CURRENT SCHOTTKY BARRIER DIODE "SuperBAT"

FEATURES

- Low V_F
- High current capability
- Miniature surface mount package


APPLICATIONS

- DC - DC converters
- Mobile telecomms
- PCMCIA

DEVICE MARKING

- Partmark detail - BD

SOD323



PINOUT - TOP VIEW



Partmark is for example only

ABSOLUTE MAXIMUM RATINGS


PARAMETER	SYMBOL	VALUE	UNIT
Continuous Reverse Voltage	V_R	40	V
Forward Current (Continuous)	I_F	400	mA
Forward Voltage @ $I_F = 400\text{mA}$	V_F	500	mV
Average Peak Forward Current; D.C. = 50%	I_{FAV}	1000	mA
Non Repetitive Forward Current	I_{FSM}	$t \leq 100\mu\text{s}$	6.75
		$t \leq 10\text{ms}$	3
Power Dissipation at $T_{amb} = 25^\circ\text{C}$	P_{tot}	250	mW
Storage Temperature Range	T_{stg}	-55 to +150	$^\circ\text{C}$
Junction Temperature	T_j	125	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ unless otherwise stated)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
Reverse Breakdown Voltage	$V_{(BR)R}$	40	60		V	$I_R = 200\mu\text{A}$
Forward Voltage	V_F		270	300	mV	$I_F = 50\text{mA}$
			300	350	mV	$I_F = 100\text{mA}$
			370	460	mV	$I_F = 250\text{mA}$
			425	500	mV	$I_F = 400\text{mA}$
			550	670	mV	$I_F = 750\text{mA}$
			640	780	mV	$I_F = 1000\text{mA}$
			810	1050	mV	$I_F = 1500\text{mA}$
			440		mV	$I_F = 500\text{mA}, T_{amb} = 100^\circ\text{C}$
Reverse Current	I_R		15	40	μA	$V_R = 30\text{V}$
Diode Capacitance	C_D		20		pF	$f = 1\text{MHz}, V_R = 25\text{V}$
Reverse Recovery Time	t_{rr}		10		ns	switched from $I_F = 500\text{mA}$ to $I_R = 500\text{mA}$ Measured at $I_R = 50\text{mA}$


ZHCS400

TYPICAL CHARACTERISTICS




ZHCS400

TYPICAL CHARACTERISTICS (Cont.)



ZHCS400

PACKAGE OUTLINE



PACKAGE DIMENSIONS

DIM	Millimeters		DIM	Millimeters	
	Min	Max		Min	Max
A	0.91	1.16	E	0.127	0.2
B	-	0.1	F	1.52	1.77
C	-	-	G	1.11	1.37
D	0.33	0.4	H	2.46	2.71

© Zetex Semiconductors plc 2004

Europe	Americas	Asia Pacific	Corporate Headquarters
Zetex GmbH Streitfeldstraße 19 D-81673 München Germany	Zetex Inc 700 Veterans Memorial Hwy Hauppauge, NY 11788 USA	Zetex (Asia) Ltd 3701-04 Metroplaza Tower 1 Hing Fong Road, Kwai Fong Hong Kong	Zetex Semiconductors plc Lansdowne Road, Chadderton Oldham, OL9 9TY United Kingdom
Telephone: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 europa.sales@zetex.com	Telephone: (1) 631 360 2222 Fax: (1) 631 360 8222 usa.sales@zetex.com	Telephone: (852) 26100 611 Fax: (852) 24250 494 asia.sales@zetex.com	Telephone (44) 161 622 4444 Fax: (44) 161 622 4446 hq@zetex.com

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to www.zetex.com



ISSUE 2 - SEPTEMBER 2004